

MOBILE OIL FILTER UNIT – MODEL E858M

SPECIFICATIONS

STANDARD VOLTAGE:

220V - 1PH - 60Hz
(other voltages available on request)

SYSTEM PERFORMANCE:

Flow rate up to 60 Usgpm
(230 L / min)
Filtration to 1/2 micron Removes
free water Stainless steel piping
option
available

Aluminum storage tank option
available

VFD option for varying flow rates



The Enervac Model E858M Mobile Oil Filter Unit is ideal for extending oil life by removal of moisture, particulate and carbon from dielectric fluids and oils used in transformers, circuit breakers, voltage regulators and switch gear. The E858M is completely mobile and certified for highway travel. The E858M can be used for retrieving the fluid, flushing and re-filling of all oil filled equipment. Operator friendliness and ease of maintenance is designed into each unit.

FEATURES:

- Robust, compact design
- Year round operation
- Suitable for highway travel
- ASME registered filter housings standard
- Can be supplied with one, two, or no storage tanks
- Self contained - Includes necessary oil hoses and power cable
- Positive displacement pumps
- All welded piping ensures less likelihood of leaks
- Single operator operation

Save disposal cost of carbon contaminated oil by restoring it to like new condition with the Enervac Model E858M. Available in many sizes and special d signs to suit your application.

Enervac Corporation
280 Holiday Inn Drive
Cambridge, Ontario
Canada
N3C 1Z4
(P)1-519-651-1034
(F)1-519-651-1038



For more
information
scan the
code!

